

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T20-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #116, dated December 16, 1866 (DCSO records Vol. 1 Page(s) 87)

Set post for corner to secs. 30, 31, 25 and 36; from which
A Maple 5" dia., bears N.37°W., 38 lks. dist.
A Maple 7" dia., bears N.45°E., 69 lks. dist.
A Maple 18" dia., bears S.35°W., 60 lks. dist.
A Hazel 3" dia., bears S.15°E., 35 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 105)

The Cor. of secs. 25, 36, 31 and 30, which is a post, 4" sq., much decayed, marked T20S S30 on NE.; R10W S31 on SE.; R11W S36 on SW.; S25 on NW. faces, with 1 notch on S. and 5 notches on N. edges, from which
A Maple 7" dia., bears N.45°E., 69 lks. dist. mkd. T20S R10W S30 BT.
A Maple 18" dia., bears S.35°W., 60 lks. dist. mkd. T20S R11W S36 BT.
A Maple 5" dia., bears N.37°W., 38 lks. dist. mkd. T20S R11W S25 BT.
A Hazel 3" dia., bears S.15°E., 35 lks. dist. mkd. T20S R10W S31 BT.

I replace the old post by setting a sandstone, 14x11x6 ins., 10" in the ground, marked with 1 notch on S. and 5 notches on N. edges.

Cor. Fd. and used in GLO resurvey by Nathaniel Martin, under Contract 599, dated June 20, 1892 (DCSO records, Vol. 1 Pages 247-248)

H.L. Eppstein - Wit: Harry Henderson; Will Dailey; Frank Cain Jan. 23, 1929 - (No record source found - see "old" corner volume 1 Pg. 7)

Set corner from old witness trees. Set stake and made mound of rocks. Marked bearing trees as follows:
Maple 10" bears S.11½°W., 66 lks.
Maple 24" bears N.45°E., 69 lks.
Maple 18" bears N.40°W., 35 lks.
No trees near in SE.

Clifford A. Stephens - For: Coos Head Timber Co. - Filed April 1958 - C.S. File 42/362 and M 10-3

(Cont. Next Page)

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T20-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Harvey Wilcox, LS #2244 - For: U.S. Forest Service
- Dec. 1990 - M 111-47 A-F

Found - 2½" brass cap on 2¼" I.P., 14' above ground, with 1"
I.P. alongside.

Orig. BT, 32" Maple, rotten face, tags, bears
N.29°W., 25.3 ft.

17" Cedar, healed face, tags, bears N.20°W., 47.3
ft.

76" Spruce visible scribed, tags, bears S.72°45'E.,
74.3 ft.

Cascara, dead, tags, bears S.72°E., 27.6 ft.

65" D.Fir, visible scribe, tags, bears S.18°W.,
70.3ft.

Set reference monument:

Standard U.S.F.S. disk, "RM T20S R10W S30 S.88°20'W
43.40' 1990 RLS 2244", bears N.88°20'E., 43.4 ft.