

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 700378

PRIMARY CORNER DESCRIPTION Sec Cor for 18 & 19 only, T20-10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 250)

-----  
At point of intersection  
A Cherry, 14" dia., on line, which I marked T20S R10W CC on E.; Sec 18 on N.; Sec 19 on S.; with 3 notches on N. and S. sides, for closing cor. to secs. 18 and 19, from which a Chittem 5" dia., bears S.30°W., 22 lks. dist. mkd. T20S R10W CC Sec 19 & 19 BT.  
Maple 6" dia., bears N.85°E., 60 lks. dist. mkd. T20S R10W Sec 18 BT.  
Chittem 6" dia., bears S.76°E., 40 lks. dist. mkd. T20S R10W Sec 18 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - April 12, 1968 - C.S. 53/66-61

-----  
Found - 1/2" I.Pipe on N-S line, unrecorded, not at point for closing cor.  
Orig. 6" now 18" Maple, alive, N.85°E., 39.6 ft. Open and find fragmentary scribe on decayed axe blaze. Rescribed "CC S18 CS BT"  
Orig. 6" now 14" Chittem, decayed stub, hollow center, S.76°E., 26.4 ft. No scribe  
No trace of other original BTs.

Set Brass cap at cor. mkd: County Surveyors Office  
R C | S18 R  
11W C | S19 10W  
1968

New BT - 28" Maple S.21°E., 41.7 ft. mkd. "T20S R10W S19 CC CS BT"

This corner lies 99.3 ft. S.3½°W. of Secs. 13 & 24, T20-11W. 1/2" I.P. bears N.85°E., 6.2 ft., creek course N. about 125 ft. East of closing corner.