

PRIMARY CORNER DESCRIPTION Sec Cor for 13 & 24 only, (East)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 107)

-----  
A Chittem tree, 6" dia., which I marked for cor. to secs. 19, 18, 24 and 13, T20S S18 on NE.; R10W S19 on SE.; R11W S24 on SW.; S13 on NW. sides, with 3 notches on N. and S. sides; from which

A Cherry 6" dia., bears N.40½°E., 34 lks. dist. mkd. T20S R10W S18 BT.

A Fir 6" dia., bears S.5½°E., 25 lks. dist. mkd. T20S R10W S19 BT.

A Fir 36" dia., bears S.81°W., 15 lks. dist. mkd. T20S R11W S24 BT.

A Fir 15" dia., bears N.74°W., 13 lks. dist. mkd. T20S R11W S13 BT.

Cor. Fd. and used in GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 244) AND on Page 250:

"I destroyed all marks on this cor. relating to R10W."

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - March/April 1968 - C.S. File 53/66-62

-----  
Found - Unrecorded 1¼" I.Pipe at corner point.  
Orig. 36" now 48" Fir, alive, S.81°W., 9.9 ft., shows bark scribe in poor condition. Rescribe "T20S R11W S24 CS BT"  
Orig. 15" now 30" Fir, N.74°W., 8.6 ft., alive, shows good scar. Do not open.

No trace of orig. corner tree, nor other BTs.

Set Brass cap at cor. mkd: County Surveyors Office

T 20 S  
R S 13 R  
11W S 24 10W  
1968

Reset Iron pipe alongside.

New BT - 15" Cedar N.56°W., 15.6 ft. mkd. T20S R11W S13 CS BT  
Corner lies on steep E. slope about 100 ft. above creek, course N. and 99.3 ft. N.3½°E., of C.C. to Secs. 18 & 19, T20-10.

Survey by P. Fox, Engineer #3282 - For: U.S. Forest Service Setp. 28, 1977 - C.S. File 60/11-37

-----  
Found - 1968 DCSO brass cap in mound of rock on steep rocky hillside. (Cont. Next Page)

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec Cor for 13 & 24 only (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

48" Fir stump with tag bears S.81°W., 9.9 ft.  
30" Fir stump with tag bears N.74°W., 8.6 ft.  
15" Cedar stump with tag bears N.50°W., 16.6 ft.  
Drilled hole in rock ledge to receive the iron pipe and a  
recess was made for the brass cap and then cemented in place.  
No new accessories.