

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 700472

PRIMARY CORNER DESCRIPTION C C for Secs. 7 & 18 only, T20-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 251)

At point of intersection, I set a sandstone 24x20x10 ins., marked CC with 4 notches on S. and 2 notches on N. edges, for closing cor. to secs. 7 and 18; from which an
Alder 6" dia., bears N.46°E., 23 lks. dist. mkd. T20S R10W Sec 7 BT.
Fir 18" dia., bears S.10°E., 16 lks. dist. mkd. T20S R10W Sec 18 BT.
Fir 10" dia., bears N.36°W., 44 lks. dist. mkd. T20S R10W Sec 7 & 18 C C BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - May 1968 - C.S. File 53/66-57

Found - 24"x20"x10" sandstone mkd. "CC+" and 2 notches on N. edge and 4 notches on S. edge, firmly set and in place.
Orig. 18" now 46" Fir, alive, S.10°E., 10.6 ft., shows good scar. We rescribe "T20S R10W S18 CC CS BT"
Orig. 10", now 28" Fir, alive, N.36°W., 29.0 ft., shows faint scar. We rescribe "CC CS BT"

Set brass cap in place of rock and mkd:

County Surveyors Office

R	T	20	S	R
11	CC		S 7	10
W			S 18	W
			1968	

New BT - 8" hemlock N.45°E., 39.2 ft. mkd. T20S R10W S7 CC CS BT.

This corner lies on top of spur ridge, sloping N. Approx. 495 ft. S. of corner to secs. 12 and 13, T20-11.

Fd. by J. Prochnau, Oct. 12, 1971 (added 7/10/2017)- M 43-56

See C.S. File 62/19, April 2, 1984 for corner information)