

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 700534

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 7 only, T20-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by James W. Prochnau - For: U.S. Forest Service - May 1971 (Revised Aug. 1971) - C.S. File 55/201-11; M 41-77 (Revised on M 43-56 - Corner #16 on Map)

Original corner never established.

At the properly proportioned position, I placed a 2" x 36" galv. I.P. flanged at the bottom and capped with a bronze disk welded on top. Monument projects 6" above ground. I filled in around the pipe monument with stone and packed earth. I stamped the disk:

| ¼ S7
1971
4185

I established new bearing trees as follows. Each BT has a scribed face and a U.S. F.S. BT sign breast high and facing the monument.

- 22" Fir bears N.29°E., 49.4 ft.
- 15" Fir bears N.78°E., 75.54 ft.

Survey by Michael J. Schwartz and L.W. Hunnemuller - For: U.S. Forest Service - Oct. 1985 - M 99-79 A&B

Found - 2" Iron pipe from Prochnau survey bears N.12°09'12"W., 2.14 ft. from corner set this survey. (Removed cap)

24" D.Fir bears N.31°E., 50.2 ft. with a healed face

16" D.Fir bears N.80°E., 75.2 ft. with a healed face

Set 3½" x 30" alum. flared pipe, with alum. cap stamped "T20S R11W R10W 1/4 S7 1985 RLS 1922".