

TOWNSHIP 20 RANGE 11 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 109)

A Willow 3" dia., which I marked $\frac{1}{4}$ S on W. side, for $\frac{1}{4}$ sec. cor.; from which

A Willow 3" dia., bears N.3°E., 4 lks. dist. mkd. $\frac{1}{4}$ S BT

A Willow 3" dia., bears S.5°W., 10 lks. dist. mkd. $\frac{1}{4}$ S BT.

Cor. Fd. in GLO survey by Nathaniel Martin, June 1892 (DCSO records, Vol. 1 Pages 247-48)

Survey by James W. Prochnau - For: U.S. Forest Service - May 1971 (revised Aug. 1971) C.S. File 55/201; M 41-77 (Revised M 43-56)

No evidence of original corner found.

At the properly proportioned position I placed a 2" x 36" galv. I.P., flanged at the bottom and capped with a bronze disk welded on top. Monument projects 6" above ground. I filled in around the pipe monument with stone and packed earth. I stamped the disk:

$\frac{1}{4}$ S12

1971

4185

I established new bearing trees as follows. Each BT has a scribed face and a U.S.F.S. BT sign breast high and facing the monument.

A 32" Fir bears S.66°W., 33.90 ft.

A 20" Fir bears N.73°W., 29.10 ft.