

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 37)

-----  
Set ¼ sec. post, from which  
A Spruce 8" dia., bears S.72°W., 6 lks. dist.  
A Spruce 24" dia., bears N.57°E., 30 lks. dist.

BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1077 - surveyed Sept. 1981/Oct 1982 - (DCSO records Vol. 44 Page(s) 17124)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an alum. post, 28" long, 2 1/2" dia., 24" in the ground, with alum. cap mkd:

T 20 S R 12 W  
1/4  
S 31 S 32  
1981

from which

A Pine 15" dia., bears N.63°E., 9½ lks. dist. mkd. ¼ S32 BT.

A Spruce 12" dia., bears S.48 3/4°W., 53 lks. dist. mkd. ¼ S31 BT.