

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. for Secs. 29, 30, 31 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 37)

Sec. post corner of secs. 29, 30, 31 and 32; from which
A Natural mound, 6 ft. high, bears N.46°W., 930 lks. dist., on top of which, Set witness corner.

BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1077 - surveyed Sept. 1981/Oct 1982 - (DCSO records Vol. 44 Page(s) 17124-25)

Point for the Sec. cor., determined by the method of two point control; there is no remaining evidence of the original corner.

Set an aluminum rod, 4 ft. long, 5/8" dia., 4 ft. in the ground, in concrete, with alum. cap mkd:

T 20 S R 12 W
S 30 S 29
S 31 S 29
1981

from which

- A Pine 5" dia., bears N.35½°E., 34½ lks. dist. mkd. X BT.
- A Pine 5" dia., bears S.47 3/4°E., 29 lks. dist. mkd. X BT
- A Pine 7" dia., bears S.20¼°W., 49 lks. dist. mkd. T20S R12W S31 BT.
- A Pine 8" dia., bears N.70¼°W., 48 lks. dist. mkd. T20S R12W S30 BT.