

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 37)

-----  
Set ¼ sec. post, from which  
A natural mound, 10 ft. high, bears N.43°45'E., 227 lks. dist., on which is witness corner.

BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1077 - surveyed Sept. 1981/Oct 1982 - (DCSO records Vol. 44 Page(s) 17126)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an alum. post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 20 S R 12 W  
1/4  
S 30 S 29  
1982

from which

A Pine 8" dia., bears S.78°E., 71 lks. dist. mkd. ¼ S29 BT  
A Fir 7" dia., bears N.46°W., 38½ lks. dist. mkd. ¼ S30 BT