

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32; and 5, T21-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 8)

-----  
Place of qr. sec. corner is on side of steep mountain.  
(Wit. Cor. placed 4.50 chs. East)

Survey by W.G. Corbitt; H. Hendrickson - For: Crown Zellerback - Aug. 4, 1943 - C.S. File 52/91

-----  
At 2+97 West of wit. cor.,  
Set 1½" I.P. and 2x2x4 Fir post, crayon mkd. "2+97 W of W.C. S32 S5 Aug. 4, 1943 by W.G. Corbitt".  
from which bears,  
8 ft. Fir N.65°W., 11.5 ft. crayon mkd. "RP 35 ft. W of  
Creek course 5 W.  
Field notes call for ridge SW at 23+10.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17193-94)

-----  
True point for the ¼ sec. cor. of secs. 5 and 32, at record distance from the original witness corner.  
Set an alum. post, 28" long, 2½" dia., 24" in the ground, with alum. cap mkd. T 20 S R 12 W  
1/4  $\frac{S\ 32}{S\ 5}$   
T 21 S  
1981

from which  
A Fir 10" dia., bears S.81°E., 16½ lks. dist. mkd. ¼ S5 BT  
A Fir 11" dia., bears N.0¼°W., 12½ lks. dist. mkd. ¼ S32 BT.

Fd. and used in BLM sec. subd. by Goodson, Tawney and Acuna, under Group #1077, surveyed Sept. 1981/Oct. 1982 - (DCSO records. Vol. 44 Pages 17160-61)