

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 37)

Set ¼ sec. post, from which
A Spruce 18" dia., bears S.2°W., 393 lks. dist.
No tree near N. of corner.

BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1077 - surveyed Sept. 1981/Oct 1982 - (DCSO records Vol. 44 Page(s) 17125-26)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an alum. post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 20 S R 12 W
1/4 S 29
S 32
1981

from which
A Pine 12" dia., bears N.22°E., 22 lks. dist. mkd. ¼ S29 BT.
A Pine 10" dia., bears S.57°W., 17 lks. dist. mkd. ¼ S32 BT.