

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 38)

Set ¼ sec. post, from which
A Willow 3" dia., bears N.46°E., 48 lks. dist.
A Willow 3" dia., bears S.85°E., 60 lks. dist.

BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1077 - surveyed Sept. 1981/Oct 1982 - (DCSO records Vol. 44 Page(s) 17128)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an alum. post, 28" long, 2 1/2" dia., 22" in the ground, with alum. cap mkd:

T 20 S R 12 W

1/4 $\frac{S\ 20}{S\ 29}$
1982

from which

A Spruce 15" dia., bears N.18½°E., 306 lks. dist. mkd. ¼ S20 BT.

A Spruce 8" dia., bears S.13¼°E., 52 lks. dist. mkd. ¼ S29 BT.