

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 39)

Set ¼ sec. post, from which
A Pine 8" dia., bears N.55°W., 180 lks. dist.
A Pine 6" dia., bears S.77°E., 118 lks. dist.

BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1077 - surveyed Sept. 1981/Oct 1982 - (DCSO records Vol. 44 Page(s) 17132-33)

Point for the ¼ sec.cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an aluminum rod, 18 ft. long, 5/8" dia., 17½ ft. in the ground, in concrete, with alum. cap mkd: T 20 S R 12 W
1/4 S 17
S 20
1982

from which
A Spruce 13" dia., bears N.60½°E., 396 lks. dist. mkd. ¼ S17 BT.
A Spruce 30" dia., bears S.37°E., 485 lks. dist. mkd. ¼ S20 BT.
Set a steel fence post alongside aluminum rod.