

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 36-37)

Set ¼ sec. post, from which
A Spruce 30" dia., bears S.79°E., 793 lks. dist.
No tree near N. of line.

BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1077 - surveyed Sept. 1981/Oct 1982 - (DCSO records Vol. 44 Page(s) 17134)

Point for the ¼ sec.cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an aluminum rod, 18 ft. long, 5/8" dia., 18 ft. in the ground, in concrete, with alum. cap mkd: T 20 S R 12 W

1/4 $\frac{S\ 8}{S\ 17}$
1982

from which
A Spruce 18" dia., bears N.89°E., 861½ lks. dist. mkd. ¼ S8 BT.
A Spruce 12" dia., bears S.67°E., 876 lks. dist. mkd. ¼ S17 BT.