

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 36)

Set 1/4 sec. post, from which
A Pine 10" dia., bears N.15°E., 230 lks. dist.
A Pine 10" dia., bears S.39 3/4°E., 235 lks. dist.

BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1077 - surveyed Sept. 1981/Oct 1982 - (DCSO records Vol. 44 Page(s) 17135)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, in concrete, with brass cap mkd: T 20 S R 12 W
1/4 $\frac{S}{S}$
1982

No suitable trees available.
Set a wooden post 8 ft. long, 4" dia., alongside iron post.