

PRIMARY CORNER DESCRIPTION W.C. to 1/4 Cor. Sec. 32; & 5, T21-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 8)

(35.50 chs.)

Witness to qr. sec. corner post, from which

A Fir 24" dia., bears N.77°W., 19 lks. dist.

A Fir 36" dia., bears S.65°W., 38 lks. dist.

(40.00 chs. West)

Place of qr. sec. corner is on side of steep mountain.

Survey by W.G. Corbitt; H. Hendrickson - For: Crown Zellerbach - Aug. 4, 1943 - C.S. File 52/91

Field notes call for W.C. at 23.43

Found - Fir BTs at W.C. and from them, relocated Wit. cor. as best I could considering distances did not check exactly. Set 1½" I.P. and 2x2x4 Fir post, crayon mkd. "WC S32 S5 Aug.4,1943", from which bears

Orig. 36" Fir now 5 ft., N.54°W., (Rec. S.65°W.) 25.08 ft. Slope -39% =23.38 to base of nail, crayon mkd. "RP BR W.C. S5". Evidently the orig. scribe marks were put on bark of tree and these were destroyed when someone cut through blaze to solid wood in 1922.

Orig. 24" Fir, now dead snag without bark, N.77°W., 13.0 ft. to nail. Old blazed face on bark indicates scribe marks were put there.

6 ft. Spruce N.65°E., 26.8 ft. 147.5 ft. -%=24.22, crayon mkd. "RP BT W.C. S32".

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17193)

The witness cor. to the ¼ sec. cor., perpetuated and recorded by Corbitt in 1943, monumented with an iron pipe, 1½" dia., firmly set, the top 12" below the surface of the ground, from which the remains of the original bearing trees:

A sawed Fir stump 58" dia., bears S.65°W., 38 lks. dist. with partially healed blaze, no marks visible.

A sawed Fir stump 26" dia., bears N.77°W., 19 lks. dist., no marks visible.

At the corner point

Set an alum. post, 28" long, 2 1/2" dia., 20" in the ground, directly over the iron pipe, with alum. cap mkd:

(Cont. Next Page)

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 244100

PRIMARY CORNER DESCRIPTION W.C. to 1/4 Cor. Sec. 32; & 5, T21-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

WC
T 21 S R 12 W
1/4 ← $\frac{S\ 32}{S\ 5}$ →
T 21 S
1981

from which
A Fir 8" dia., bears N.58½°E., 15 lks. dist. mkd. X BT.
A Fir 8" dia., bears S.58¼°E., 16 lks. dist. mkd. X BT.
This corner now becomes an angle point.