

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 300202

PRIMARY CORNER DESCRIPTION M.C. W. bdy. Sec. 28

Alias <u>958160</u>	Description <u>M.C. bdy. Lake Tahkenitch</u>
Alias <u> </u>	Description <u> </u>
Alias <u> </u>	Description <u> </u>
Alias <u> </u>	Description <u> </u>

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 32)

To Lake Tahkenitch. A Spruce 8" dia. is meander corner, from which

A Spruce 60" dia., bears S.26°W., 5 lks. dist.

A Spruce 30" dia., bears S.62°E., 40 lks. dist.

BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1077 - surveyed Sept. 1981/Oct 1982 - (DCSO records Vol. 44 Page(s) 17114-15)

The meander cor. of secs. 28 and 29, on the S. shore of Tahkenitch Lake, determined from the remains of the original bearing trees:

A rotted Spruce stump 32" dia., bears S.62°E., 34 lks. dist. with scribe marks S28 T29S R12W visible on open blaze. (Record and slope dist., 40 lks.)

A sawed Spruce stump 60" dia., bears S.26°W., 5 lks. dist. with axe marks visible.

At the corner point

Set an aluminum rod, 4 ft. long, 5/8" dia., 30" in the ground, with alum. cap mkd: MC S29 S28 T20S R12W 1981, from which new bearing trees:

A Fir 6" dia., bears S.12°E., 7½ lks. dist. mkd. T20S R12W S28 MC BT.

A Spruce 7" dia., bears S.30°W., 12½ lks. dist. mkd. T20S R12W S29 MC BT.