

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 33)

Set ¼ sec. post, from which
A Spruce 24" dia., bears N.10°E., 17 lks. dist.
A Spruce 36" dia., bears S.73°W., 8 lks. dist.

Survey by W.G. Corbitt - For: Crown Zellerbach - April 13, 1943 - C.S. File 52/91

Found orig. BTs North, scribes covered.
Reset corner with 1½" I.P. and 2"x2"x6 ft. Fir post crayon mkd. "S20|S21 W.G. Corbitt, April 13, 1943" from which bears,
Orig. 36" Spruce now 5 ft. D.Fir, S.73°W., 5.28 ft. to nail between scribe "BT". Rest covered.
Orig. 24" Spruce now 4 ft., N.10°E., 7.8 ft. to head of boat spike protruding from root of tree. All scribes covered. Too much to cut into.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage, crew - June 1971 - C.S. File 53/66-32

Found - 1½" I.P. at ¼ corner, badly rusted.
36" Spruce, not D.Fir stump, S.73°W., 5.3 ft., previously open scribe, found part of "B".
24" Spruce, now 4 ft. stob, N.10°E., 11.2 ft. As noted 7.8 ft. to boat spike in boot of tree. Set 1943 by W.g. Corbitt.
Call of 1 chain North to top of ridge, hits good.
Set brass cap at ¼ cor. alongside I.P. mkd: County Surveyors Office, 1971 T20S R12W ¼ S20|S21
New BTs -6" D.Fir S.87°E., 30.5 ft. scribed ¼ S21 CS BT.
16" Spruce S.58°W. scribed ¼ S20 CS BT.
Also found 1½" Iron pipe, N.52°E., 39.0 ft.
Best way to reach corner, good luck. Run South from Crown Zellerbach gate.

Cor. Fd. and used in BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1077 - surveyed Sept. 1981/Oct 1982 - (DCSO records Vol. 44 Page(s) 17115)

Survey by William Shull, LS #909 - For: U.S. Forest Service -March 20, 1985 - M 98-67

Found - 1" I.P. with brass cap, loose, 12" exposed. I mounded soil and compacted around it.
(Cont. Next Page)

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

40" Spruce stump N.32°E., 9.8 ft. blaze visible.
(Rec. BLM N.21°E., 17 lks.)
48" Fir stump S.76°W., 6.5 ft. blaze, no scribing
visible. (BLM rec. S.73°W., 8 lks.)
18" Fir S.88°E., 29.9 ft. healed blaze. (Rec. 15"
Fir, S.87½°E 45 lks. BLM)
22" Spruce S.60°W., 20.4 ft. healed blaze. (Rec.
21", S.59½°W., 31 lks. BLM)
Set 2½" USFS alum. monument, N.88°39'W., 49.2 ft. 3" exposed.
Cap stamped "¼ S20 RM S88°39'E 49.2' 1985 LS 909" with arrow
pointing to corner.