

PRIMARY CORNER DESCRIPTION Sec Cor for 16, 17, 20 and 21

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 34)

-----  
Set Post corner of secs. 16, 17, 20 and 21, from which  
A Spruce 24" dia., bears S.45°W., 15 lks. dist.  
A Spruce 36" dia., bears N.63°W., 73 lks. dist.  
A Spruce 12" dia., bears N.24°E., 30 lks. dist.  
A Fir 18" dia., bears S.67°E., 70 lks. dist.

Survey by W.G. Corbitt - For: Crown Zellerbach - April 3, 1943 - C.S. File 52/91

-----  
Found 1½" Iron pipe and 1"x1"x5 ft. stake, crayon mkd. from which bears:

Orig. 18" Fir now 22", S.68°E., 46.1 ft. to nail scribed S21 T20S R12W. BT covered.

Orig. 12" Spruce now 18" Fir, deand and down, N.25°E., 24.0 ft. to nail scribed S16 T20S R12W. BT covered.

Orig. 36" Spruce now 36" live Fir tree, N.62°W., 51.9 ft. to nail in overgrowth which covers all scribe marks.

Orig. 24" Spruce now 36" dead and down Fir, HN NE S.78°30'W., 9.6 ft. to nail in overgrowth covering all scribes.

I blazed 5 ft. Spruce tree, S.86°15'W., 19.65 ft. to + in top of RR spike, crayon marked blaze "S20 RP BT".

I blazed 5 ft. Spruce stump S.22°15'E., 34.9 ft. to ¾" in top of RR spike, crayon mkd. S21 RP BT - Corbitt

Set 2"x2"x6 ft. Spruce post crayon mkd. S17 S16 S20 S21 ^P 186+26.8 in iron pipe.

Timber logged in sec. 16, 21 and 20.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage, crew - June 16, 1971 - C.S. File 53/66-33

-----  
Found - 1½" I.P, badly rusted at section corner.

18" D.Fir now 22" stob, S.67°E., 46.2 ft. Scribe visible "T20S R12W S21". Opened BT scar for scribe "BT". Very old scribing.

1943 5 ft. Spruce stump, S.22°E., 34.9 ft. to R.R. spike.

No trace of other nails set or original BTs.

Possible original Fir stump N.63°W., 51.9 ft. (Rec. 48.2 ft.)

Set brass cap alongside I.P. mkd: County Surveyors Office

(Cont. Next Page)

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec Cor for 16, 17, 20 and 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

|  |
|--|
| <p>T 20 S<br/>S 17   S 16<br/>S 20   S 21<br/>R 12 W<br/>1971</p> <p>New BT - 7" Fir S.31°W., 15.7 ft. scribed T20S R12W S20 CSBT<br/>No other trees available.</p>  |
| <p>BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1077 - surveyed Sept. 1981/Oct 1982 - (DCSO records Vol. 44 Page(s) 17116)</p> <p>-----</p> <p>The sec. cor., perpetuated and recorded by Powell in 1971, monumented with an iron pipe 1½" dia., firmly set, projecting 12" above ground, with 1971 brass cap.<br/>from which the remains of the original bearing trees<br/>A Fir snag 18" dia., bears S.67°E., 70 lks. dist., with scribe marks S21 T20S R12W visible on opened double blaze.<br/>A root hole bears S.45°W., 15 lks. dist. alongside of which is lying a Spruce, size indeterminate, no marks visible.<br/>and a bearing tree mkd. by Powell<br/>A Fir 15" dia., bears S.29°W., 24 lks. dist., with healed blaze.<br/>and new bearing trees<br/>A Spruce 17" dia., bears S.70½°E., 102 lks. dist. mkd. T20S R12W S21 BT.<br/>A Pine 20" dia., bears N.78°W., 80 lks. dist. mkd. T20S R12W S17 BT.</p> |
| <p>Survey by William Shull - For: U.S. Forest Service - March 20, 1985 - M 98-67</p> <p>-----</p> <p>Found - 1½" iron pipe with brass cap 12" exposed.<br/>18" Fir snag, S.67°E., 46.2 ft. scribed "S21 T20S R12W".<br/>Root hole, S.45°W., 9.9 ft.<br/>15" Fir, S.29°W., 15.8 ft., healed blaze.<br/>17" Spruce S.70½°E., 67.3 ft., healed blaze.<br/>20" Pine, N.78°W., 52.8 ft., healed blaze.<br/>Set USFS alum. monument, N.78°36'W., 48.5 ft.<br/>New BT - 4½" Hemlock N.29°E., 18.3 ft., scribed "X BT".</p>  |
| <p>Fd. OK, April 1995 by R. Ward - M 122-3 B</p>   |
| <p style="text-align: right;">2</p>  |