

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 34)

Qr. sec. corner, post omitted.

BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1077 - surveyed Sept. 1981/Oct 1982 - (DCSO records Vol. 44 Page(s) 17117)

Point for the ¼ sec. cor. of secs. 16 and 17, at proportionate distance; no corner was established during the original survey.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 20 S R 12 W
1/4
S 17 S 16
1982

from which

A Fir 10" dia., bears N.86°E., 7 lks. dist. mkd. ¼ S16 BT

A Spruce 10" dia., bears S.54°W., 11½ lks. dist. mkd. ¼ S17 BT.

Fd. OK April 1995 by R. Ward - M 122-4