

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 34)

- Corner of secs. 8, 9, 16 and 17. Set post, from which
- A Spruce 36" dia., bears N.2°W., 25 lks. dist.
  - A Spruce 40" dia., bears S.70°W., 9 lks. dist.
  - A Spruce 36" dia., bears S.24°E., 31 lks. dist.
  - A Spruce 15" dia., bears N.86°E., 67 lks. dist.

Survey by W.G. Corbitt - For: Crown Zellerbach - Jan. 7, 1941 C.S. File 52/91

Found bearing trees to corner.  
 Set 1½" I.P. using orig. field notes from which now bears 2x2x4½ Spruce stake E. side of pipe:

- 36" Spruce stump N.2°W., 16.5 ft. scribe marks R12W.
- 48" Spruce stump S.70°W., 6.0 ft. covered.
- 44" Spruce stump S.24°E., 20.5 ft. covered.
- 24" Spruce stump N.86°E., 44.2 ft. rotten face.

This corner is in logged land and has never been relocated. No cruiser's marks found. Corner stands on ridge about 3 chs. South of edge of swamp.

BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1077 - surveyed Sept. 1981/Oct 1982 - (DCSO records Vol. 44 Page(s) 17118)

The Sec. cor., perpetuated and recorded by Corbitt in 1943, monumented with an iron pipe, 2" dia., firmly set, projecting 6" above ground, from which the remains of the original bearing trees:

- A sawed Spruce stump 25" dia., bears N.86°E., 68 lks. dist. with illegible scribe marks visible on open blaze. (Record and to face, 67 lks.)
- A sawed Spruce stump 44" dia., bears S.24°E., 34 lks. dist. no marks visible on opened blaze. (Rec. 31 lks.)
- A sawed Spruce stump 46" dia., bears S.70°W., 12 lks. dist., no marks visible on open blaze. (Rec. 9 lks.)
- A sawed Spruce stump 36" dia., bears N.2°W., 27 lks. dist. with scribe marks T20 R12W visible on partially opened blaze. (Rec. 25 lks.)

At the corner point  
 Set an alum. post 28" long, 2½" dia., 24" in the ground, with alum. cap mkd:

T	20	S	R	12	W
		S	8	S	9
		S	17	S	16
			1982		

from which new bearing trees (Cont. Next Page)

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Spruce 14" dia., bears N.57°E., 34 lks. dist. mkd. T20S R12W S9 BT.  
A Spruce 15" dia., bears S.61°E., 7 lks. dist. mkd. T20S R12W S16 BT.  
A Hemlock 10" dia., bears S.45½°W., 30 lks. dist. mkd. T20S R12W S17 BT.  
A Fir 7" dia., bears N.58°W., 39 lks. dist. mkd. T20S R12W S8 BT.  
Reset iron pipe alongside aluminum post.

Fd. OK, April 1995 by R. Ward - M 122-4