

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 35)

-----  
Set ¼ sec. post, from which  
A Spruce 36" dia., bears S.45°W., 12 lks. dist.  
A Spruce 36" dia., bears S.69°E., 18 lks. dist.

Survey by W.G. Corbitt - For: Crown Zellerbach - April 5, 1943 - C.S. File 52/91

-----  
Found original BTs and reset ¼ corner.  
Set 1½" I.P. from which bears:  
Orig. 36" Spruce now 48" at marks, S.62°E., 10.56 ft. to nail scribed "BT". Rest covered.  
Orig. 36" Spruce S.40°W., 7.92 ft. to nail, now 48" at marks, scribed "¼ S", rest covered.  
Set 2"x2"x6 ft. crayon mkd. post, "¼ S8 S9 W.G.Corbitt 1943"

BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1077 - surveyed Sept. 1981/Oct 1982 - (DCSO records Vol. 44 Page(s) 17119-20)

-----  
The ¼ sec. cor., perpetuated and recorded by Corbitt in 1943, monumented with an iron pipe, 2" dia., firmly set, projecting 10" above ground, from which the remains of the original bearing trees:

A sawed Spruce stump 41" dia., bears S.69°E., 18 lks. dist. with scribe marks BT visible on partially opened blaze.

A sawed Spruce stump 41" dia., bears S.45°W., 12 lks. dist. with scribe mark 4 visible on partially opened blaze.

At the corner point

Set an aluminum post, 28" long, 2½" dia., 21" in the ground, with alum. cap mkd:

T 20 S R 12 W  
1/4  
S 8 S 9  
1981

from which new bearing trees

A Spruce 5" dia., bears N.45½°E., 29 lks. dist. mkd. ¼ S9 BT.

A Spruce 13" dia., bears N.74½°W., 17 lks. dist. mkd. ¼ S8 BT.

Reset iron pipe alongside aluminum post.

(Cont. Next Page)

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by William Shull, LS #909 - For: U.S. Forest Service  
-April 10, 1985 - M 98-69

-----  
Found - 1981 BLM 2" alum. cap, top extending 7" above ground  
41" Spruce stump S.69°E., 12.2 ft. scribe marks "BT"  
visible in partially open blaze. (41" Spruce  
stump S.69°E., 18 lks. BLM)  
41" Spruce stump S.45°W., 9.3 ft. scribe mark "4"  
visible partially open blaze. (41" Spruce stump,  
S.45°W., 12 lks. BLM)  
5" Spruce N.45½°E., 19.2 ft., healed blaze (5"  
Spruce N.45½°E., 29 lks. BLM)  
13" Spruce N.72½°W., 11.0 ft., healed blaze. (13"  
Spruce N.74½°W., 17 lks. BLM)  
Set 2¼" USFX x 30" alum. monument with 3¼" alum. cap with  
magnet attached under cap. Cap mkd. "¼ S8 RM S34°32'E. 49.6'  
1985 LS 909" with arrow pointing to corner. Cap bears  
N.34°32'W., 49.6 ft. with 2" exposed.