

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec Cor for 4, 5, 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 35)

Margin of lake. Set post, corner of secs. 4, 5, 8 and 9, from which

A Willow 6" dia., bears S.84°W., 120 lks. dist.

Alder 3" dia., bears S.81°E., 136 lks. dist.

Alder 10" dia., bears N.49°E., 142 lks. dist.

Douglas Co. Surveyors Office - John Powell - June 16, 1971 - C.S. File 53/66-36

No trace of any cor. found. Location poster, (how located?)
Cor. card sent in by Smith River Ranger District.

BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1077 - surveyed Sept. 1981/Oct 1982 - (DCSO records Vol. 44 Page(s) 17120)

Point for the cor. of secs. 4, 5, 8 and 9, and meander cor. on the E. shore of Carter Lake, determined by extending the line westerly from the ¼ sec. cor. of secs. 4 and 9, through a point, hereinafter described, established by Stoddart, Engineer for the Bureau of Public Roads, in 1931, at a distance recorded by Stoddart to the cor. of secs. 4, 5, 8 and 9, when original evidence was in existence.

Set an iron post 28" long, 2½" dia., 25" in the ground, in concrete, with brass cap mkd: T 20 S R 12 W

MC S 5 | S 4
 S 8 | S 9
 1982

from which

An Iron post 28" long, 2½" dia., set 27" in the ground, for a reference monument, bears N.63°E., 58 lks. dist., with brass cap mkd. RM T20S R12W S4 38.3 FT. TO COR 1982, and an arrow pointing to the corner.

An iron post 28" long, 2½" dia., set 27" in the ground, for a reference monument, bears S.27°E., 48½ lks. dist. with brass cap mkd. RM T20S R12W S9 32 FT TO COR 1982, and an arrow pointing to the corner.

Corner is located on the E. shore of Carter Lake, edge bears N.30°E. and S.30°W.