

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 36)

Set ¼ sec. post, from which
A Pine 8" dia., bears S.7¼°E., 734 lks. dist.
A Pine 15" dia., bears N.8½°W., 813 lks. dist.

Survey by Karl F. Foeste - For: Crown Zellerbach; Sparrow-Pacific Corp. and U.S. Forest Service - Nov. 25, 1974 - C.S. File 58/25; M 49-80 and M 56-1

Found - Orig. SW BT scribed by Gordon in 1858. It is now 26" Fir snag, but was called an 18" Pine in U.S. notes, scribing is visible.
At record distance of 536.58 ft. and record bearing of N.2°45'E., from said BT:
I set flush, a 2" x 36" concrete filled galv. I.P. with a 3" brass cap fully stamped, from which I set:
9" Pine bears N.45°W., 40.9 ft. to face scribed "¼ S 5 BT"
10" Pine bears S.89°30'W., 27.8 ft. to face scribed "¼ S5 BT"

BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1077 - surveyed Sept. 1981/Oct 1982 - (DCSO records Vol. 44 Page(s) 17122-23)

The ¼ sec. cor., perpetuated and recorded by Foeste, in 974, monumented with an iron post, 2" dia., firmly set flush with the ground, with brass cap mkd: LS 849 1/4 S5 S4 1974, from which the remains of an original bearing tree
A Fir snag, 26" dia., bears S.2 3/4°W., 813 lks. dist. with scribe marks BT visible on remains of blaze. (Record, Pine)
and bearing trees mkd. by Foeste
A Pine 12" dia., bears S.89 3/4°W., 42 lks. dist. with scribe marks ¼ S5 BT visible on open blaze.
A Pine 11" dia., bears N.43¼°W., 62 lks. dist., with scribe marks ¼ S5 BT visible on open blaze.

From this point, a point established and recorded by Forrest A. Colling, RLS #880, in 1972, bears S.1°35'W., 2.56 chs. dist. monumented with an iron pipe 2" dia., firmly set, projecting 1" above ground, from which bearing trees mkd. by Colling
A Pine 10" dia., bears S.51°W., 98 lks. dist., no marks visible on open double blaze. (Cont. Next Page)

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

A Pine 12" dia., bears N.60½°W., 69 lks. dist., no marks visible on open double blaze.