

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 33; and 4 of T21-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 7)

Set qr. sec. post, from which
A Spruce 60" dia., bears S.75°E., 80 lks. dist.
A Spruce 30" dia., bears N.67°E., 112 lks. dist.

Survey by W.G. Corbitt; H. Hendrickson - For: Crown Zellerbach Corp. - Aug. 21, 1943 - C.S. File 52/91

No BTs found, so set:
Pipe at proportional distance between MC 33 and 4 and corner for 32, 33, 5 and 4.

Robert Ward, L.S. #1091 - For: Siuslaw National Forest & Tahkenitch Tree Farm Partnership - April 1995 - M 122-3 A

Found - Corbitt's 1½" I.P,
REPLACED pipe with a 2½" x 30" Alum.
cap mkd: T20S R12W ¼ S33 S4 T21S 1994 LS 1091, from
which
BTs - 18" Spruce, bears N.45°E., 22.1 ft. (¼ S33 BT)
30" D.Fir, bears S.50°E., 8.0 ft. (¼ S4 BT)
10" Spruce, bears S.4°E., 19.4 ft. (X BT)
10" Spruce, bears S.13 3/4°W., 13.6 ft. (¼ S4 BT)