

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 29)

Set post corner of secs. 9, 10, 15 and 16, from which

A Spruce 50" dia., bears S.13°E., 40 lks. dist.

A Spruce 50" dia., bears S.17°W., 37 lks. dist.

A Spruce 50" dia., bears N.31°W., 27 lks. dist.

A Spruce 60" dia., bears N.28°E., 31 lks. dist.

December 18, 1857

Survey by W.G. Corbitt; Paul Krugur; N. Seethoff; B. Senn -
For: Crown Zellerbach - Jan. 9, 1941 - C.S. File 52/91

Found iron marks on root of 60" Spruce, N.26°E., 21.0 ft.

Found iron marks on 40" Spruce, S.8°E., 26.5 ft.

I did not have original notes.

Set 1½" I.P., 1/2 ft. protruding next to the stake found.

Iron marks face the stake.

Many large Spruce about close to stake. Stake is in the lowest place at the head of a small ravine. Cruiser's marks "E.J."