

PRIMARY CORNER DESCRIPTION Sec Cor for 3, 4, 9 and 10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 30)

Set post corner of secs. 3, 4, 9 and 10, from which
A Hemlock 4" dia., bears S.65°E., 36 lks. dist.
A Hemlock 4" dia., bears S.27°W., 15 lks. dist.
A Hemlock 4" dia., bears N.39°W., 36 lks. dist.
A Spruce 36" dia., bears N.60°E., 100 lks. dist.

GLO survey by Wm. H. Byars, Deputy Surveyor, under Contract #745, dated May 1, 1902 - (DCSO records Vol. 1 Page(s) 79)

The cor. of secs. 3, 4, 9 and 10, the post and witness trees to this cor. are all destroyed, excepting the Spruce 36" dia., bearing N.60°E., 100 lks. dist., it is down, but yet recognizable. I reestablish this cor. by marking a Hemlock, 8" dia., T20S S3 on the NE.; R12W S10 on the SE.; S9 on the SW.; and S4 on the NW. faces and 5 notches on the S. and 3 notches on the E. angles of the same; from which
A Hemlock 8" dia., bears N.45°E., 17 lks. dist. mkd. T20S R12W S3 BT.
A Hemlock 24" dia., bears S.60°E., 18 lks. dist. mkd. T20S R12W S10 BT.
A Hemlock 16" dia., bears S.40°W., 26 lks. dist. mkd. T20S R12W S9 BT.
A Chittenwood 5" dia., bears N.65°W., 48 lks. dist. mkd. T20S R12W S4 BT.
In place of the old witness tree, A Spruce 36" dia, bears N.60°E., 100 lks. dist.

Survey for Crown Zellerbach - C.S. File 52/91 (Page 7)

(Jan. 8, 1941)
P. Krugur and N. Seethoff did not have orig. notes but set 1½" I.P. NE of 8" Hemlock snag squared on 4 sides with scribe marks on all 4 sides, from which
8" Hemlock windfall N.58°E., 10.0 ft., scribe marks.
An old stake was found 1.5 ft. N. of squared tree. This area has been logged and burned.
(March 20, 1943)
Corbitt and Elliott found 1½" I.P., N.35°E., 1.5 ft., from which
8" Hemlock snag squared 4 sides broken off, scribed.
Moved Iron pipe back to center of rotten stump. 8" Hemlock that was scribed on 4 sides from which now bears:
10" Hemlock N.46°E., 12 ft. scribed S3 T20S R12W, dead and leaning NW.
Other original BTs missing. (Cont. Next Page)

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec Cor for 3, 4, 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

6 ft. Spruce stump, 10 ft. high, N.30°E., 65.7 ft. to nail, crayon mkd. S3 T20S R12W BT. Cedar stake in top of stump.

60" Spruce stump S.2°W., to nail in top of stump, 71.9 ft., no marks.

Corner stands South of cat road about 40 ft.. Logged and burned around here.

1x4x5 ft. Cedar stake in I.P. crayon mkd. S4 S3 S9 S10 T20S R12W 1943.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage, crew - June 16, 1971 - C.S. File 53/66-35

Found - 1902 24" Hemlock, down, burnt, S.60°E., 11.9 ft.
16" Hemlock, down, burnt, S.40°W., 17.6 ft. Old burnt axe marks old face.

1943, 1½" Iron pipe set at section corner. (C.S. File 52/91)

60" Spruce stump, S.2°W., 71.9 ft. No nail found.

72" Spruce stump, N.30°E., 65.7 ft. No nail found

Set brass cap alongside 1½" Iron pipe marked:

County Surveyors Office

T 20 S R 12 W

S 4 | S 3

S 9 | S10

1971

New BTs -14" D.Fir S.83°W., 7.6 ft. scribed T20S R12W S9 CSBT

7" Cedar N.11°W., 3.1 ft. scribed T20S R12W S4 CS BT

10" D.Fir N.60°E., 12.7 ft. scribed T20S R12W S3 CS BT.

8" Hemlock S.12°E., 20.8 ft. scribed T20S R12W S10 CS BT.

Fd. and used in BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1077 - surveyed Sept. 1981/Oct 1982 - (DCSO records Vol. 44 Page(s) 17110)

Fd. OK, April 1995 by R. Ward - M 122-4