

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 34; and 3 of T21-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 7)

Set qr. sec. post, from which
A Hemlock 18" dia., bears N.70°W., 4 lks. dist.
A Spruce 30" dia., bears S.44°E., 19 lks. dist.

Survey by W.G. Corbitt; C. Boatman; J.K. Elliott - For: Crown Zellerbach Corp. - April 2, 1943 - C.S. File 52/91

Found - Orig. Spruce BT with scribe marks.
Reset 1½" I.P. and 3"x3"x5 ft. Spruce post, crayon mkd. "S34 S3 ¼ T20S R12W T21S R12W 1943", from which bears
Orig. 30" Spruce stump S.44°E., 12.54 ft. to nail scribed ¼ S BT marks are covered.
Orig. 18" Hemlock has been pulled out in construction of cat road.
I marked:
36" Spruce stump N.58°E., 27.4 ft. to nail, in blazed face, crayon mkd. "¼ S34 RP BT".
NE corner about 25 ft. East of cat road.

Clyde Mulkins, surveyed for: Port Blakely Tree Farms; Scott Timber Co.; Menasha Corp. July 1997 - M 127-39.

Set - 5/8" x 36" rebar with a 2" alum. cap, from which:
Found - The remains of the original 30" spruce (only fragments of scribing remain) bears S.55°E., 12.54 ft.
Set a 5/8" x 30" rebar with a plastic cap mkd. "LS 2006" in the center of the stump remains:
2" iron pipe, bears N.89°E., 5.7 ft.
New Accessories -
11" D.Fir, bears N.49°W., 39.6 ft. scribed "¼ S34 BT"
16" Hemlock, bears S.37°W., 56.5 ft. scribed "¼ S3 BT"
5 ft. steel fence post bears N.58°E., 14.1 ft.
5 ft. steel fence post bears N.25°E., 0.80 ft.
Note - The corner falls 3 ft. south from top of cut bank of old overgrown road.