

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 27)

Set ¼ sec. post, from which
 A Spruce 24" dia., bears N.45°W., 30 lks. dist.
 A Spruce 6" dia., bears S.33°E., 18 lks. dist.

Survey by W.G. Corbitt; Paul Krugur; N. Seethoff; B. Senn -
For: Crown Zellerbach - March 22, 1943 - C.S. File 52/91

Chained West from M.C. and at 2675.6 ft., arrived at a point where we relocated the ¼ corner from a 24" Spruce stump which we took to be orig. 24" Spruce BT. This is a stump of old snag which was blazed and marked with one axe notch like the BT at M.C.

Set 2"x2"x6 ft. Spruce limb for ¼ cor. S22 S27 W.C. Corbitt, 1943, from which bears:

- Orig. 24" Spruce stump N.45°W., 198 ft., nail in notch.
- 6 ft. Spruce stump N.7°E., 22.2 ft. blazed crayon mark "S22 RP BT"
- 4 ft. Spruce stump S.7°W., 34.2 ft. blazed crayon mark "S27 RP BT"

Corner is 33 ft. East of cat road on ridge.