

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 31)

-----  
A Hemlock 18" dia., qr. sec. corner, from which  
A Hemlock 18" dia., bears S.20°W., 13 lks. dist.  
A Hemlock 18" dia., bears N.2°E., 30 lks. dist.

Survey for Crown Zellerbach - C.S. File 52/91 (Page 8)

-----  
(April 9, 1943)  
Corbitt and Elliott found one orig. BT and reset corner with 1½" Iron pipe 3x3x8 ft. Cedar post, crayon mkd. "¼ S3 S10 W.G.Corbitt 1943", from which bears:  
24" Cedar stump N.16°30'E., 37.3 ft. to boat spike crayon mkd. ¼ S3 RPBT.  
30" Cedar snag S.4°W., 27.2 ft. to boat spike crayon mkd. ¼ S10 RPBT.  
Orig. 18" Hemlock dead and down, N.16°W., 24.5 ft. ¼ S  
\_\_\_\_notch.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage, crew - June 16, 1971 - C.S. File 53/66-34

-----  
Found - 1943 trees and 1½" I.Pipe set by Corbitt. (CS File 52/91)  
Cedar snag, S.4½°W., 27.3 ft. Nail in face.  
Cedar stump N.16°E., 37.3 ft. Nail in face.  
No trace of any original BTs.  
New BTs -12" Spruce S.25°W., 17.9 ft. scribed ¼ S10 CS BT.  
7" Alder N.34°E., 9.0 ft. scribed ¼ S3 CS BT.

Survey by Karl F. Foeste - For: Crown Zellerbach; Sparrow Pacific Corp.; and U.S. Forest Service - Nov. 25, 1974 - C.S. File 58/25; M 49-80 and M 56-1

-----  
Found - 1½" I.P. set by Corbitt in 1943.  
Corbitt's 30" Cedar snag, bears S.4°W., 27.2 ft. to boat spike.  
Corbitt's 24" Cedar stump, bears N.16½°E., 37.3 ft. to boat spike.  
DCSO 8" Alder now dying, bears N.36°E., 8.6 ft. to scribed face.  
DCSO 13" Spruce bears S.24°W., 17.4 ft. to scribed face.  
I remove Corbitt's I.P. and:  
Set a 2" x 36" concrete filled galv. I.P. with 3" brass cap fully stamped, from which:  
(Cont. Next Page)

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>7" Spruce bears N.24°E., 34.1 ft. to face, scribed "¼ S3 BT".</p>
<p>Fd. and used in BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1077 - surveyed Sept. 1981/Oct 1982 - (DCSO records Vol. 44 Page(s) 17109-10)</p>
<p>Fd. OK April 1995 by R. Ward - M 122-4</p>