

PRIMARY CORNER DESCRIPTION M.C. on W. bdy. Sec. 3

Alias <u>956430</u>	Description <u>M.C. on bdy. Siltcoos Lake</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 31)

-----  
Set meander corner, from which  
A Hemlock 14" dia., bears S.53°E., 19 lks. dist.  
A Hemlock 24" dia., bears N.69°E., 27 lks. dist.

-----  
Survey by W.G. Corbitt; H. Hendrickson - For: Crown Zellerbach - April 14, 1943 - C.S. File 52/91

-----  
Found orig. BTs and 6x6x3 ft. Cedar post scribed CS MC called for at 15.60 chs. As the position of post did not check with notes, I set 1½" x 4 ft. I.Post on S. side of post from which bears:

Orig. 14" Hemlock now 18" and dead but standing, S.63°E., 12.54 ft. to boat spke, scribed BT, rest covered. Cruiser's marks "X".

Orig. 24" Hemlock now 30" stump N.69°E., 17.82 ft. to boat spike scribed R12W. The upper portion has been cut off. BT covered.

I mark with crayon, 30" Cedar, S.19°15'E., 13.1 ft. to nail "S10 MC RP BT"

Set 2x2x5 ft. Cedar limb in Iron pipe.

-----  
Survey by Karl F. Foeste - For: Crown Zellerbach; Sparrow Pacific Corp.; and U.S. Forest Service - Nov. 1974 - C.S. File 58/25 and M 56-1

-----  
Found Corbitt's 1½" x 4 ft. Iron pipe set in 1943, from which Orig. 14" Hemlock, now an 18" snag, bears S.63°E., 12.5 ft. to boat spke in face scribed "BT".

Orig. 24" Hemlock now 30" stump, has been moved by cat. Corbitt's 30" Cedar bears S.19°E., 13.0 ft. to nail in face.

I removed Corbitt's iron pipe and in its place set a 2" x 36" concrete filled galv. iron pipe with 3" brass cap fully stamped, from which I set one new bearing tree;

20" Cedar bears S.26°E., 14.2 ft. to face scribed "MC S10 BT"

-----  
BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1077 - surveyed Sept. 1981/Oct 1982 - (DCSO records Vol. 44 Page(s) 17108)

-----  
The middle meander cor. of ses. 3 and 10, on shore of Siltcoos Lake, perpetuated and recorded by Corbitt in 1943, subsequently perpetuated and recorded by Foeste, in 1974,

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 464600

PRIMARY CORNER DESCRIPTION M.C. on W. bdy. Sec. 3

Alias <u>956430</u>	Description <u>M.C. bdy. Siltcoos Lake</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

monumented with an iron pipe 2" dia., firmly set, projecting  
4" above ground, with brass cap mkd: LS 849

T 20 S

/S 3

/ S 10

R 12 W

1974

from which the remains of an original bearing tree

A Hemlock snag 18" dia., bears S.63°E., 19 lks. dist.,  
with scribe marks S10 T20S R12W T visible on open  
blaze. (Rec. S.53°E.)

and a bearing tree mkd. by Corbitt

A Cedar 28" dia., bears S.19°E., 21½ lks. dist., no marks  
visible on open blaze.

and a bearing tree mkd. by Foeste

A Cedar 20" dia., bears S.29°E., 23 lks. dist., with  
scribe marks MC S10 BT visible on partially healed  
blaze.

and a new bearing tree

A Hemlock 7" dia., bears N.67°W., 58 lks. dist. mkd. T20S  
R12W S3 MC BT.

Fd. OK, April 1995 by R. Ward - M 122-4