

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 15)

-----  
Spruce 10" dia. is qr. sec. corner; from which  
A Fir 18" dia., bears S.60°W., 28 lks. dist.  
A Spruce 30" dia., bears N.45°E., 3 lks. dist.

-----  
Survey by W.C. Corbitt; B. Senn; Paul Kruger and N. Seethoff  
- For: Crown Zellerbach - Feb. 4, 1941 - C.S. File 52/91

-----  
Found original BTs.  
Set 1½" I.P., 2 ft. West of 14" Spruce snag which stands for  
¼ corner. From Spruce snag bears:  
48" Spruce stump, N.45°E., 2.0 ft.  
Rotten stump, S.60°W., 28.5 ft.

-----  
(Report from Dec. 12, 1941) (C.S. File 52/91)  
W.C. Corbitt and B. Senn found I.P. 2 ft. W. of orig. 10"  
Spruce, which is now 18" dead snag blazed & scribed ¼S on W.  
side. I put nail in blazed face. Orig. 30" Spruce BT is cut  
off, cross section of stump shows scar of blazed face. No  
scribe marks visible.  
Corner stands N. 50 ft. from cat road on ridge, E & W.