

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 15)

Set post corner of secs. 26, 27, 34 and 35, from which
A Spruce 48" dia., bears S.88°W., 99 lks. dist.
A Spruce 24" dia., bears N.61°W., 54 lks. dist.
A Spruce 30" dia., bears S.64°E., 17 lks. dist.
Alder 12" dia., bears N.14°E., (dist. omitted)

Survey by W.C. Corbitt; B. Senn; Paul Krugur; N. Seetholff -
For: Crown Zellerbach - Feb. 3, 1941 - C.S. File 52/91

Found original BTs.
Set 1½" I.P. from which bears,
60" Spruce stump, N.61°W., 37 ft., marks covered.
40" Spruce stub, N.89°W., 68 ft., scribed S34 T20S R.
50" Spruce stump S.64°E., 11.2 ft. scribed. Cruiser's
marks, "LB".

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 4/21/94 - C.S. File 64/51-3

Found - 1½" I.D. iron pipe protruding 8" above ground.
24" now 60" dia., 10' high spruce stump no blazes or
scribing visible, bears N.66½°W., 43.5' to root
crown (rec. N.61°W., 35.6' is a possible blaze
measurement) Orig. BT.
40" now 48" dia., 8' high rotted spruce stump with
scribing visible "34" bears S.88°W., 73.2' to
root crown (rec. S.88°W., 65.3' is a blaze
measurement) Orig. BT.
30" now 50" dia., 8' high spruce stump with
illegible scribe mark visible in a previously
opened blaze bears S.64°E., 12.7' (rec. S.64°E.,
11.2' is a blaze measurement) Orig. BT.

Set 2 3/8" dia., brass cap on a 1 3/8" O.D. iron pipe is set
at referenced position of 1½" I.P. BC/IP protrudes 7" above
ground. Stamped:

DOUGLAS COUNTY SURVEYORS

T20S	R
<u>S27</u> <u>S26</u>	1
S34 S35	2
1994	W

OFFICE

1½" I.P. measured 27' long when removed is set along North
edge of BC/IP, protrudes 7" above ground.

New Accessories:

(Cont. Next Page)

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

6" dia., Spruce, double blazed "T20S R12W S27 CS BT" bears N.34°W., 29.1'.

24" dia., 2' high Hemlock stump with boat spike through BT tag set near center on top BS stamped "B02", BS S.2°E., 36.4'.

30" dia., 1½" high Spruce stump with Boat spike through BT tag set near center on top, BS Stamped "B01" BS bears N.83½°E., 38.8'.

26" dia., 1½' high Hemlock stump with Boat spike through BT tag set near center on top, BS stamped "B03" BS bears S.58½°W., 17.9'.

See C.S. File for sketch.

Note: Corner lies in a new clear cut.

Found OK 8/94 by Stuntzner - M120-75 A-D; C.S. 63/145.