

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 17-18)

Set ¼ sec. post, from which
 An Alder 24" dia., bears East, 16 lks. dist.
 Yellowwood 6" dia., bears S.21°W., 18 lks. dist.

Survey by Warren D. Hootman - For: Crown Zellerbach Corp. - July 28, 1960 - C.S. File 51/165 and M 11-77

Proportioned distance 471.5 ft. South 0°43' East of the N. meander corner of secs. 22 and 23 by driving an iron pipe and marking the following bearing trees:

 D.Fir 6" DBH, bears N.60°45'E., 13.6 ft.

 D.Fir 5" DBH, bears N.19°00'W., 17.9 ft.

This corner lays on an East slope approx. 145 ft. West of the creek.

Survey by Ronald Stuntzner - For: Tahkenitch Tree Farm - Aug. 1994 - M120-75 A-D and C.S. File 63/145.

Found - 3/4" iron pipe (M11-77).
 20" Fir stump bears N.19°W., 17.9 ft., scribed "BT" on new face.

Set 3/4" x 30" iron rod with 2" aluminum cap marked "Stuntzner Engineering ¼ S22 S23 1994 LS 1342". Set in the center of iron pipe.

New BTs - 22" Fir stump face scribed "BT" bears N.85°E., 8.6 ft. to center.

 75" Spruce stump bears S.78°E., 43.2 ft. to center, not tagged or marked.

 60" Spruce stump bears N.19°W., 58.3 ft. to center, not tagged or marked.