

PRIMARY CORNER DESCRIPTION M.C. on W. bdy. Sec. 23

Alias <u>960850</u>	Description <u>M.C. So. shore Lake Tahkenitch</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 18)

Set post, from which
 A Spruce 30" dia., bears S.19°W., 15 lks. dist.
 A Spruce 30" dia., bears East, 62 lks. dist.

Survey by W.C. Corbitt - Crew: B. Senn; Paul Krugur; N. Seethoff; J.K. Elliott - For: Crwon Zellerbach - May 3, 1943
C.S. File 52/91

Found Rotten stubs of 2 Spruce trees which fit the position of BTs called for in field notes, from these I relocated the M.C.

Set 1½" I.P. and 2"x2"x5 ft. Spruce post, crayon mkd. "Approx. M.C. S22-S23 1943", from which

 Orig. 30" Spruce, now only rotten stub and roots without blazes or scribe marks, East 40.9 ft. to stake. Set where face of trees was assumed to have been.

 Orig. 30" Spruce, now rotten stub and roots without blazes or scribe marks S.19°W., 9.9 ft. to where face of tree assumed to have been.

I marked:

 4 ft. Spruce stump S.69°E., 70.5 ft. to nail set in large opening 1½" I.P. in top of this stump. About 8 ft. SE of this stump is 8 ft. Spruce stump.

This corner in swamp and submerged when water high in lake.

Survey by Warren D. Hootman - For: Crown Zellerbach - July 28, 1960 (filed Jan. 1961) - C.S. File 51/165 and M 11-77

On South shore of Tahkenitch Lake. This point is an iron pipe in a swamp. I re-witness this corner as follows:

 An Alder 9" DBH, bears S.50°30'E., 29.3 ft.

 An Alder 11" DBH, bears S.16°30'W., 62.3 ft.