

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 20)

-----  
Set qr. sec. post, from which  
A Fir 30" dia., bears N.70°E., 3 lks. dist.  
A Spruce 24" dia., bears N.19°W., 22 lks. dist.

Survey by W.G. Corbitt and B. Senn - For: Crown Zellerbach - Oct. 28, 1941 - C.S. File 52/91

-----  
Found original BTs at ¼ corner.  
Set 1½" I.P. and 3"x3"x6 ft. Fir post, from which bears  
Orig. 30" Fir, stump, N.70°E., 1.98 ft. Scribed face has been burnt out but overgrowth scar shows where BT scribe should be.  
Orig. Spruce 24", N.19°W., 14.5 ft. has only portion of rotten stump left in ground. No marks visible.

I blazed:  
24" Spruce stump, N.79°W., 23.1 ft. to nail, crayon mkd. "BT ¼ S15".

Old blazed line N. to road about 400 ft., 428 ft. to ridge NE. and SW.

Stuntzner Engineering & Forestry - For: Western Pacific Timber Survey - November 15, 1992 - M 116-32

-----  
Found - 1½" inside dia. rusted iron pipe.  
30" Original Fir stump with burnt face, visible scribe, tag, bears N.70°E. 2.0 ft. to face.  
24" Spruce stump rotten to ground, tag, bears N.79°W. 23.1 ft. to face (CS 52/91)

New BTs- 10" Fir stump, "X" chop, tag, bears N.08°E. 3.52 ft.  
18" Fir stump, "X" chop, tag, bears S.85°W. 15.40 ft  
Set Bearing Object - 4 ft. aluminum post bears N.23°E 2.0 ft.  
Set - 3/4" x 30" iron rod, set inside iron pipe, with 2" alum. cap marked: ¼  
S15 S14  
1992  
LS 1342

Found OK 8/94 by Stuntzner - M120-75 A-D; C.S. File 63/145.