

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 20)

Set post, corner of secs. 10, 11, 14 and 15, from which
A Spruce 36" dia., bears S.27°E., 31 lks. dist.
A Spruce 30" dia., bears N.79°E., 23 lks. dist.
A Spruce 8" dia., bears S.56°W., 57 lks. dist.
A Spruce 24" dia., bears N.88°W., 1.25 chs. dist.

Stuntzner Engineering & Forestry - For: Western Pacific
Timber Survey - November 15, 1992 - M 116-32

Set - 3/4" x 30" iron rod with 2" alum. cap marked:
T20S R12W
S10 S11
S15 S14
1992
LS 1342

New BTs- 28" Cedar face scribed "S10 BT" with "X" chop at
breast height, tag, bears N.04°W. 29.15 ft.
32" Spruce face scribed "S11 BT" with "X" chop at
breast height, tag, bears N.39°E. 33.0 ft.
15" Hemlock face scribed "S14 BT" with "X" chp at
breast height, tag, bears S.83°E. 5.15 ft.
19" fir face scribed "S15 BT" with "X" chop at
breast height, tag, bears S.67°W. 17.85 ft.