

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 534400

PRIMARY CORNER DESCRIPTION W. M.C. between Secs. 14 & 23

Alias <u>961010</u>	Description <u>M.C. bdy. Lake Tahkenitch</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 18)

Set post, from which
A Fir 24" dia., bears N.65°E., 6 lks. dist.
A Fir 24" dia., bears S.65°E., 5 lks. dist.

Survey by W.G. Corbitt; B. Senn - For: Crown Zellerbach - March 30, 1943 - C.S. File 52/91

Found both BTs at M.C. called for at 34.15 chs. Using dist. given in notes, the cor. was relocated with:
Set 1½" I.P. and 2"x2"x5 ft. Spruce post, crayon mkd. MC S14 S23 1943, from which bears:
Orig. 24" Fir now (?) S23, dead, S.56°E., 3.3 ft. to nail scribed S23 T20S R12W BT covered.
Orig. 24" Fir, now dead snag, N.77°30'E., 3.96 ft. to nail scribed S14 T20S R12W BT remains covered.
Corner stands in thick patch of huckleberry.

Survey by Warren D. Hootman - For: Crown Zellerbach - July 28, 1960 (filed Jan. 1961) - C.S. File 51/265 and M 11-77

I calculate the position by a series of triangulations locating the approx. position of this corner on the lake shore. I find the 2 original bearing trees with visible scribing and the corner point marked by a pipe. Both bearing trees are short snags. I mark new bearing trees as follows:
Hemlock 6" DBH, bears N.74°30'E., 45.3 ft.
Hemlock 6" DBH, bears S.82°15'E., 64.4 ft.