

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 15)

A Fir 24" dia., is qr. sec. corner; from which
A Vine Maple 6" dia., bears N.5°E., 20 lks. dist.
A Fir 18" dia., bears S. W., 22 lks. dist.

Survey by Ronald Stuntzner - For: Tahkenitch Tree Farm - August 1994 - M120-75A-D and C.S. File 63/145.

Found 58" Fir stump (Original corner tree).
Set 3/4" x 30" iron rod with 2" aluminum cap marked "Stuntzner Engineering 1/4 S26 S35 1994 LS 1342" in stump.

Found BTs -

A leaning 44" Fir stump, bears S.69°W., 14.5 ft. to a point where center of stump would be if leaned back into position. (Original BT)

New BTs -

13" Spruce, face scribed "S¼ S26 BT" with X-chop and tag at B.H. bears N.13°W., 8.9 ft. to a spike at side center.

11" Cherry, bark scribed "S¼ S26 BT" with X-chop and tag at B.H. bears N.76°E., 8.2 ft. to spike at side center.

27" Spruce, face scribed "N¼ S35 BT" with X-chop and tag at B.H. bears S.57°W., 32.0 ft. to a spike at side center.