

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 17)

-----  
Set ¼ sec. post, from which  
    A Spruce 36" dia., bears S.25°W., 25 lks. dist.  
    An Alder 24" dia., bears N.62°E., 47 lks. dist.

Survey by W.C. Corbitt, crew, B. Senn; Paul Krugur; N. Seethoff; J.K. Elliott - March 25, 1943 - C.S. File 52/91

-----  
Run East from Lake Tahkenitch and at 2601 ft. found a stake set for ¼ ocr.  
I set 1½" I.P. for corner, and 2"x2"x5 ft. post, from which  
    Orig. 36" Spruce (really a 44" D.Fir) S.25°W., 16.50 ft.  
    to nail scribed ¼ S. Ring count checked for orig. survey.  
    The orig. 36" Alder no longer exists therefore I mkd:  
    24" Spruce N.63°E., 29.5 ft. crayon mkd. ¼ S23 RP BT.  
This corner stands at head of gulch 60 ft. E. of N. & S. ridge on W-E-S from this corner. cruiser's marks NE X = = and 2 checks.

Survey by Warren D. Hootman - For: Crown Zellerbach Corp. - July 28, 1960 (filed Jan. 1961) - C.S. File 51/165 and M 11-77

-----  
I identify from the original bearing trees. Corner point is marked by a pipe. I mark one new BT as follows:  
    Spruce 28" DBH bears N.53°00'W., 29.3 ft.  
    The original BT bears S.22°00'W., 16.5 ft. measured to the face; the tree is dead at this time.  
The corner lays on an East slope approx. 60 ft. East of the top of the ridge. Timber in the SE quad. has been cut in recent times.

Survey by Ronald Stuntzner - For: Tahkenitch Tree Farm - Aug. 1994 - C.S. File 63/145 and M 120-75 A - D

-----  
Found 1½" Iron pipe.  
    28" Spruce stump with healed face and tag, bears N.53°E., 29.3 ft.  
    44" Fir stump with visible scribe and tag bears S.25°W., 16.5 ft. (Orig. BT)  
Set ¾" x 30" Iron rod with 2" alum. cap mkd. "Stuntzner Engineering ¼ S23 S26 1994 LS 1342".  
(Cont. Next Page)

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs -16" Spruce, face scribed "S ¼ S23 BT" with X-chop and tag at B.H., bears N.65°E., 12.9 ft. to a spike at side center.  
15" Fir, face scribed "N ¼ S23 BT" with X-chop and tag at B.H., bears S.50°E., 22.1 ft. to a spike at side center.