

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 18)

Set ¼ sec. post, from which
A Fir 18" dia., bears N.71°E., 27 lks. dist.
A Spruce 18" dia., bears S.25°E., 34 lks. dist.

Survey by W.G. Corbitt and B. Senn - For: Crown Zellerbach - April 10, 1943 - C.S. File 52/91

Corbitt and Elliott measured East 390 ft. from M.C. bet. 14 and 23 and set 2"x2"x5 ft. Spruce post in approx. location of ¼ cor. for 14 and 23, as the orig. 18" Fir BT has been pushed over in logging and moved from its original position, although the depression where it stood still remains. From this post, bears:

- 30" Spruce stump N.61°E., 30.9 ft. to nail mkd. RP 1½" pipe in top of stump.
 - 48" Spruce stump S.81°W., 15.9 ft. to spike mkd. R.P.
- The 18" Fir snag BT shows scribe marks ¼ S BT. I put nail in face of blaze.

The E. & W. blazed line seems to run South of M.C.

Survey by Warren D. Hootman - For: Crown Zellerbach - July 28, 1960 (filed Jan. 1961) - C.S. File 51/165 and M 11-77

I find the pipes set by Corbitt and the 2 Spruce stumps blazed by him and the remains of the original D.Fir BT.
I re-witness this corner by marking:
D.Fir 7" DBH, bears S.12°00'W., 17.7 ft.
Spruce 4" DBH, bears N.33°00'E., 6.5 ft.

Survey by Ronald Stuntzner - For: Tahkenitch Tree Farm - Aug. 1994 - M120-75 A-D and C.S. File 63/145.

Found - A 2" pipe as shown in M11-77.
30" spruce stump bears N.61°E., 32.8 ft. to center, (rec. N61°E., 30.9 ft.)
27" Fir with healed face and tag bears S.12°W., 16.9 ft. to side center, (rec. S.12°W., 17.7 ft.)
48" Spruce stump bears S.81°W. 17.8 ft. (rec. S.81°W., 15.9 ft.)
Set A 3/4" x 30" iron rod with 2" alum. cap mkd "Stuntzner Eng. ¼ S14 S23 1994 LS 1342". Placed in the cen. of the 2" IP New BT - 18" Hemlock face scribed "N 1/4 S23 BT" with X-chop and tag at B.H. bears S.57°E., 7.0 ft. to spike at side center.