

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 578300

PRIMARY CORNER DESCRIPTION CC for Secs. 23 & 24 only (South)

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Wm. H. Byars, Deputy Surveyor, under Contract #745, dated May 1, 1902 - (DCSO records Vol. 1 Page(s) 68)

At the point of intersection (N. bdy. Sec. 26),
Set a Hemlock post 4 ft. long, 4" sq., 24" in the ground for closing cor. of secs. 23 and 24 mkd. CC T20S R12W on N.; S24 on E.; and S23 on W. faces, with 2 grooves on S. and 1 groove on E. faces, from which
A Spruce 28" dia., bears N.20°E., 40 lks. dist. mkd. T20S R12W S24 BT.
A Hemlock 30" dia., bears N.23½°W., 30 lks. dist. mkd. T20S R12W S23 BT.

Survey by Warren D. Hootman - For: Crown Zellerbach Corp. - Jan. 30, 1963 - C.S. File 51/249-1 and M 22-36

On the North line of Sec. 26, which is also an iron pipe witnessed by the original bearing trees:
28" Spruce N.20°E., 26.40 ft.
30" Hemlock N.23½°W., 19.8 ft.

Survey by Ronald Stuntzner - For: Tahkenitch Tree Farm - August 1994 - M120-75 A-D and C.S. File 63/145.

Found - 1" iron pipe.
Set 3/4" x 30" iron rod with 2" aluminum cap marked "Stuntzner Engineering T20S R12W S23 S24 CC 1994 LS 1342"
Found BTs -
30" rotten Hemlock stump bears N.23°30'W., 19.8 ft. to face (Original BT)
46" Fir snag with visible scribe and tag bears N.79°E., 17.9 ft.
New BTs -21" Fir, face scribed "CC S24 BT" with X-chop and tag at B.H. bears N.39°E., 22.2 ft. to spike at side center.
14" Spruce, face scribed "CC S23 BT" with X-chop and tag at B.H. bears N.74°W., 13.0 ft. to spike at side center.

Fd. BC/IP, & 4 BTs, Brent Bacon, 9/2005 - M148-53