

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 12)

Set ¼ sec. post, from which
A Cedar 18" dia., bears S.18°W., 14 lks. dist.
A Yellowwood 6" dia., bears N.82°E., 21 lks. dist.

Survey by W.G. Corbitt and R.L. Follett - For: Crown Zellerbach - Oct. 14, 1943 - C.S. File 52/91

Opened old blaze on Hemlock and found scribe marks. Relocated corner.

Set 1½" I.P. and 3"x3"x5 ft. Spruce post mkd. "¼ S S35|S36 R.L. Follett W.G. Corbin Oct. 14, '43", from which

Orig. 16" Cedar now 24" Hemlock snag, S.18°W., 9.24 ft. to nail, scribed "¼".

6 ft. Fir N.35°W., 9.25 ft. to nail, crayon mkd. "RP BT ¼ S35 RLF".

6 ft. Fir S.6°30'E., 43.7 ft. to nail, crayon mkd. "RP BT ¼ S36 RLF"

This corner stands on side hill 40 ft. E. of small gulch and Krugur's Tined line where cruiser Srotschy signed up at false corner, Dec. 4, 1942.

Ronald Stuntzner - For: Tahkenitch Tree Farm - Aug. 1994 - M120-75 A-D and C.S. File 63/145.

Found - 2" iron pipe (C.S. File 52/91).
Set ¾" x 30" iron rod with 2" aluminum cap marked "Stuntzner Engineering ¼ S35 S36 1994 LS 1342". Set inside 2" I.pipe

Found - 83" Fir stump with visible scribe bears S.6°30'E., 43.7 ft. to nail in face. (C.S. File 52/91)

48" Fir stump with tag bears N.35°W., 9.25 ft. to nail in face. (C.S. File 52/91)

Possible cedar root bowl bears S.18°W., 9.24 ft. (Orig. BT)

New BTs- 19" Hemlock, face scribed "W¼ S36 BT" with X-chop and tag at B.H. bears N.75°E., 3.82 ft. to a spike at side center.

10" Hemlock, face scribed "E¼ S35 BT" with X-chop and tag at B.H. bears S.2°W., 9.76 ft. to a spike at side center.

Found OK by B. Bacon, Oct. 2002 - M141-23