

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 26 only (North)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 13-14)

A Hemlock 12" dia. is corner of secs. 23, 24, 25 and 26, from which

- A Spruce 36" dia., bears N.55°W., 13 lks. dist.
- A Spruce 30" dia., bears S.30°W., 10 lks. dist.
- A Spruce 36" dia., bears S.65°E., 20 lks. dist.
- A Fir 36" dia., bears N.86°E., 51 lks. dist.

GLO survey by Wm. H. Byars, Deputy Surveyor, under Contract #745, dated May 1, 1902 - (DCSO records Vol. 1 Page(s) 67-68)

(Intersect E. & W. line, 130 lks. West of old Sec. cor.), Post and one witness tree destroyed. Reestablish cor. by setting a Hemlock post, 4 ft. long, 4" sq., 24" in the ground and mkd. T20S S24 on the NE.; R12W S25 on the SE.; S26 on the SW.; and S23 on the NW. faces, also 2 notches on the S. and 1 notch on the E. edges; from which

- A Spruce 36" dia., bears N.66°E., 51 lks. dist.
- A Spruce 36" dia., bears S.65°E., 20 lks. dist.
- A Spruce 36" dia., bears N.55°W., 13 lks. dist.
- A Spruce 48" dia., bears S.76°W., 40 lks. dist. mkd. T20S R12W S26 BT. This tree is in place of the one destroyed.

Destroyed all markings referring to secs. 23 and 24 on the old corner and its witnesses.

Survey by Warren D. Hootman - For: Crown Zellerbach Corp. - Jan. 30, 1963 - C.S. File 51/249 and M 22-36

Said point being a 1" Iron pipe and witnessed by the original bearing trees as follows:

- 36" Spruce N.66°E., 33.66 ft.
- 38" Spruce S.65°E., 13.20 ft.
- 36" Spruce N.55°W., 8.58 ft.
- 48" Spruce S.76°W., 26.40 ft.

Said point being 5229.90 ft., N.89°34'W. of the section corner for secs. 24 and 25.

Survey by Ronald Stuntzner - For: Tahkenitch Tree Farm - August 1994 - M120-75A-D and C.S. File 63/145.

Found - 1" iron pipe inside the rusted remains of a 3" iron pipe.

Set 3/4" x 30" iron rod with 2" aluminum cap marked "Stuntzner Engineering T20S R12W S24 S25 S26 1994 LS 1342" at position of 1" iron pipe. (Cont. Next Page)

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. cor. for 25 & 26 only (North)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Found - 36" Spruce stump bears N.55°W., 8.58 ft. (Orig BT)
48" Spruce stump bears S.76°W., 26.4 ft. (Orig BT)
New BTs -16" Fir, face scribed "T20S R12W S24 BT" with X-chop
and tag at B.H. bears N.58°E., 9.0 ft. to spike
at side center.
14" Hemlock, face scribed "T20S R12W S26 BT" with X-
chop and tag at B.H. bears S.74°W., 22.6 ft. to
spike at side center.