

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GL0 survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 18-19)

- 
- Set post corner of secs. 13, 14, 23 and 24, from which
- A Spruce 36" dia., bears S.52°W., 48 lks. dist.
  - A Vine Maple 6" dia., bears S.21°E., 51 lks. dist.
  - A Fir 30" dia., bears N.3°W., 78 lks. dist.
  - A Fir 30" dia., bears N.4°E., 67 lks. dist.

GL0 survey by Wm. H. Byars, Deputy Surveyor, under Contract #745, dated May 1, 1902 - (DCSO records Vol. 1 Page(s) 66)

- 
- Cor. post destroyed, witness trees standing and agree with notes furnished by the surveyor general. I reestablish the corner with a Spruce post from witness trees, 4 ft. long, 4" sq., 24" in the ground mkd. T20S S13 on NE.; R12W S24 on SE.; S23 on SW.; and S14 on NW. faces, with 3 notches on S. and 1 notch on E. edges; from which
- A Spruce 36" dia., bears S.52°W., 48 lks. dist.
  - A Vine Maple 6" dia., bears S.21°E., 51 lks. dist.
  - A Fir 30" dia., bears N.3°W., 78 lks. dist.
  - A Fir 30" dia., bears N.4°E., 67 lks. dist.

Survey by W.G. Corbitt; R.L. Follett - For: Crown Zellerbach March 29, 1943 - C.S. File 52/91

-----

I found orig. BTs as described. Since distance did not check with field notes, I reset corner (not Frey's stake) with a 1½" I.P. and 2"x2"x5 ft. Fir post, crayon mkd. "S14 S13 S23 S24 1943", from which

- Orig. 30" Fir now 36", N.4°E., 43 ft. to nail scribed S13 T20S BT is on root to East.
- Orig. 30" Fir now 40", N.3°W., 52 ft., scribe marks covered so could not reach the orig. face. Cruiser's mark V.
- 48" Fir North, 48 ft. stands between other 2 Fir BTs.
- Orig. 36" Spruce, now 36", S.52°W., 29 ft. to nail scribed "S23 T20S R12W". Most of scribe marks remain covered. The annual ring count shows this tree was scribed in 1857 so must be one of the BTs for the first corner established here. A 5 ft. Spruce bears S.31°30'W., 26.2 ft. to nail below old blaze.
- Orig. 6" Vine Maple S.23°E., 28.8 ft. to crack in trunk. Tree bent over.

This corner stands in gulch on N. side of ridge. Few trees around.

(Cont. Next Page)

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Warren D. Hootman - For: Crown Zellerbach Corp. -  
Jan. 30, 1963 - C.S. File 51/249-1 and M 22-36

-----  
Sec. cor. is a 1½" Iron pipe witnessed by three of the orig.  
bearing trees as follows:

- 56" Spruce S.52°W., 31.7 ft.
- 42" D.Fir N.3°W., 51.5 ft.
- 44" D.Fir N.4°W., 44.2 ft.

Survey by Clyde Mulkins, LS #2008 - For: Sparrow-Pacific and  
Richard Holmes - Oct. 30, 1987 - M 101-31

-----  
Found - A 4" square white post very rotted at base, bears NW  
0.5 ft. (No monument found)

- 30" Spruce N.25°W., 38.2 ft. with healed face.
- Orig. 36" D.Fir snag, N.4°E., 43 ft. to face with  
visible scribe.
- 60" Spruce stump, S.31°30'W., 26.2 ft. with tag.
- Orig. 36" Spruce stump S.52°W., 29.0 ft. with  
visible chop marks.
- Orig. BT, 46" D.Fir snag, N.3°W., 52.0 ft. Face not  
opened. Cruiser marks.
- 30" Spruce of unknown origin with healed face,  
N.25°W., 38.2 ft.

Set 3/4" x 30" rebar with 2" alum. cap based on W.G. Corbitt  
1943 measurements.

- New BTs -15" Hemlock scribed "S13 T20S R12W BT" bears N.3°W.,  
38.1 ft.
- 32" Spruce scribed "S24 T20S R12W BT" bears S.1°E.,  
43.6 ft.
- 6" Hemlock scribed "X BT" bears S.79°W., 5.1 ft.

Fd. OK Aug. 1992, by R. Stuntzner - M 120-75 A-D.  
Fd. BC/IP, & 7 BTs, Brent Bacon, 9/2005 - M148-53