

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. H. Byars, Deputy Surveyor, under Contract #745, dated May 1, 1902 - (DCSO records Vol. 1 Page(s) 69 and 73)

Set temp. 1/4 sec. cor.
Set a Maple post 4 ft. long, 4" sq., 24" in the ground, for the 1/4 sec. cor. marked 1/4 S14 on the W. and S13 on the E. faces, from which
 A Spruce 48" dia., bears East, 40 lks. mkd. 1/4 S13 BT.
 A Spruce 30" dia., bears N.62°W., 32 lks. mkd. 1/4 S14 BT.

Survey by W.G. Corbitt; B. Senn; Paul Krugur; N. Seethoff - For Crown Zellerbach - March 29, 1943 - C.S. File 52/91

Found orig. BTs at 1/4 corner and relocated the corner based on dist. as bearings did not check.
Set 1 1/2" I.P. and 2"x3"x4 ft. Spruce post, crayon mkd. "S14 S13 1943", from which
 Orig. 48" Spruce (really a 1/4S double tree 24" and 18" dead snag), N.77°30'E., 26.4 ft. to nail scribed "1/4 S BT"
 Orig. 30" Spruce now 40", N.43°30'W., 21.1 ft. to nail, scribe marks remain covered.
 The 14" Hemlock BT for old corner bears N.88°E., about 70 ft.
Krugur did not find correct corner when he blazed line, 1941.

Survey by Clyde Mulkins, LS #2008 - For: Sparrow-Pacific and Richard Holmes - Oct. 30, 1987 - M 101-31

Found - 1 1/2" Iron pipe.
 20" Fir N.34 1/2°E., 92.5 ft. with healed face.
 Hemlock stump, N.18 1/2°E., 53.0 ft. to face. (Rec. S.10°W., 45.5 ft.)
Replaced I.P. with 3/4" x 30" rebar with 2" alum. cap.
New BTs -22" Spruce N.28°E., 6.6 ft.
 11" Hemlock S.44°E., 43.1 ft.

Fd. OK August 1994 by Stuntzner - M 120-75 A-D

Tony Hostetter - For: Roseburg Resources Co. - Sept. 1999 - M 133-40

Found - 3/4" iron rod w/alum. cap & BTs as described by Mulkins, 1987
New BT- 20" Hemlock, scribed "S14 1/4 BT" bears N.18°W., 46.0' to spike in root collars, below face. BT tag.
 6 ft. fence post 1 ft. north.