

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 620640

PRIMARY CORNER DESCRIPTION Center West 1/16 cor. Sec. 1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Perry Fox L.S. #1457 - For: Davidson Industries, Inc. - June 1981 - C.S. File 58/238(n) and M 88-13

-----  
Set 2½" brass cap, from which  
26" Fir N.82°W., 8.7 ft.  
25" Spruce S.29°E., 11.5 ft.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - July 26, 1988 - C.S. File 62/64 and M 101-51 (Map filed April 1989)

-----  
Found - A 2½" dia. brass cap on a 2¼" O.D. Iron pipe, protrudes 8" above ground.  
26" now 29" dia. D.Fir with an axed "X" upper blaze and a partially healed lower blaze with illegible scribing visible, bears N.82°W., 8.0 ft. (Rec. N.82°W., 8.7 ft. to center of trunk)  
25" now 28" dia. Spruce with an axed "X" upper blaze and a partially healed lower blaze, no scribing visible, bears S.29°E., 11.5 ft. (agrees w/rec)  
Set a 2½" dia. DCS0 brass cap on a 1 3/8" O.D. x 32" long iron pipe, protruding 6" above ground, from which  
29" dia. D.Fir with an axed "X" upper blaze and partially healed lower blaze with illegible scribing visible bears S.65°W., 8.6 ft. (Blaze faces S.82°E) (BT, M 88-13)  
28" dia. Spruce with an axed "X" upper blaze and partially healed lower blaze, no scribing visible, bears S.22°E., 15.8 ft. (BT, M 88-13)  
1981 2½" dia. BC/IP bears S.1°E., 4.7 ft.  
This monument bears N.68°05'51"E., 196.76' from 1964 location  
See C.S. 62/64, Corner #3 for BTs fd. of the 1964 location.