

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 36; and 1, T21-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 5)

Set qr. sec. post; from which
A Cedar 18" dia., bears S.31°E., 18 lks. dist.
An Alder 12" dia., bears N.50°W., 8 lks. dist.

Survey by Ronald Durham - For: Menasha Corp. - March 1965 - C.S. File 51/311

Drive 2" x 3 ft. alum. pipe, 2 ft. into the ground, from which
45" Red Cedar bears S.31°E., 11.9 ft. Orig. BT, face has been chopped out.
New BT:
34" Fir bears N.21½°E., 35.0 ft. scribed S36 BT.
24" Fir snag bears N.17°W., 23.7 ft. with a tag and painted red.

Survey by Richard J. Hintz - For: Champion International and International Paper - March 1980 - C.S. File 58/140 and M 79-30

Found - 2" alum. pipe and 45" Cedar BT stump. Durham's new BTs are gone, probably destroyed during the subsequent logging.
I place an alum. tag on a 36" Fir stump which bears S.47°W., 25.7 ft.

Troy Rambo - For: Port Blakely Tree farms - March/April 2002 - M140-7

Found - The record stumps per CS file 58/140 in place & in poor condition.
New - Scribed "¼ S36 BT" on 12" DF, bears N.27°E., 27.1 ft
Scribed "¼ S36 BT" on 11" DF, bears N.66°E., 18.0 ft
Scribed "¼ S1 BT" on 8" RC, bears South 20.7 ft.
Scribed "¼ S1 BT" on 13 DF, bears S.33°W., 16.7 ft.

Found OK by B. Bacon, Oct. 2002 - M141-23