

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 14)

Set qr. sec. post, from which
A Fir 12" dia., bears N.15°W., 27 lks. dist.
A Fir 15" dia., bears S.12°W., 50 lks. dist.

GLO survey by Wm. H. Byars, Deputy Surveyor, under Contract #745, dated May 1, 1902 - (DCSO records Vol. 1 Page(s) 76)

Post gone, both witness trees standing and agree with field notes furnished by the surveyor general. I reestablish the cor. by a Spruce tree, 5" dia., which I mark ¼ S24 on N. and ¼ S25 on S. sides.

Survey by Warren D. Hootman - For: Crown Zellerbach Corp. - Jan. 30, 1963 - C.S. File 51/249 and M 22-36

Set on line between the sec. cors. and at the proportioned distance. 1/4 corner is a 1" brass capped pipe witnessed by:
5" Alder S.5°W., 9.0 ft.
Spruce stump N.85°E., 12.0 ft.