

TOWNSHIP 20 RANGE 12 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias	Description

GLO survey by Wm. H. Byars, Deputy Surveyor, under Contract #745, dated May 1, 1902 - (DCSO records Vol. 1 Page(s) 66-67)

Set a Spruce post, 4 ft. long, 4" sq., 24" in the ground, for the ¼ sec. cor., mkd. ¼ S13 on the N. and 24 on the S. faces, from which

 A Spruce 30" dia., bears S.44°W., 15 lks. dist. mkd. ¼ S24 BT.

 A Spruce 12" dia., bears N.46½°W., 15 lks. dist. mkd. ¼ S13 BT.

Survey by Warren D. Hootman - For: Crown Zellerbach Corp. - Jan. 30, 1963 - C.S. File 51/249-1 and M 22-36

Set 1" brass capped pipe, witnessed as follows:

 8" Hemlock S.70°W., 30.5 ft.

 32" Spruce N.60°W., 50.6 ft.

This corner is about 10 ft. West of the West cut slope of the Forest Service Road.

Fd. OK Oct. 30, 1987 by C. Mulkins - M 101-31

Tony Hostetter - For: Roseburg Resources Co. - Sept. 1999 - M 133-40

Found - 1" iron pipe w/brass cap & BTs as described by Mulkins, 1987

New BT - 20" Hemlock scribed "S14 ¼ BT", bears N.22°28'E., 48.54 ft. to spike.